

WP6D152E200 G-Drive Engine Data Sheet

Speed	Gross Engine Output		
	COP	PRP	ESP
rpm	kWm	kWm	kWm
1500	117	138	152

Ratings Definitions

	Continuous Power (COP)	Prime Power (PRP)	Standby Power (ESP)
Mean engine load factor	100%	≤70% per 250 h	≤80% per 24 h
Annual working time	Unlimited	Unlimited	≤200 h
Time at full load	Unlimited	≤500 h per year	≤25 h per year
Overload capacity	No	1 h per 12 h (10% overload)	No

- 1) The power ratings are in accordance with ISO 3046.
- 2) Test conditions: 100 kPa, 25 °C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L.
- 3) The engine maybe operated at : up to 1000m and 30 °C without power deration. For sustained operation above these conditions, derate by 3% per 300m, and 2% per 11 °C.
- 4) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.

Engine basic data

Engine model	WP6D152E200	Cylinder number	6
bore diameter /stroke mm	105 ×130	Displacement(L)	6.75
Fuel System	Mechanical Pump	Aspiration	Turbocharged and Aftercooled
Compression Ratio	18:1	Emission Standard	Off-road stageII
Overall Dimension (Length×Width×Height) (mm)	1302×688×1059	Engine net weight (kg)	625±50
Injection timing (°CA)	8.5±0.5		
Flywheel housing	SAE 1/SAE3	Flywheel	11.5"
Max. Permissible Fixing Angle (°)	Longitudinal Inclination	Front /Rear	10/10
	Cross Inclination	Left/Right	10/10
Dynamic angle (°)	Longitudinal Inclination	Front/Rear	/
	Cross Inclination	Exhaust pipe side /Intake pipe side	/

Permitted temperature ambient °C	-30~50	Permitted altitude limit m	2000
Valve lashes at cold (mm)	Intake: 0.20+0.05 Exhaust 0.30+0.05		

Performance Data

Idle Speed (rpm)	650±25	Over Speed limit (rpm)	1575
Mean Piston Speed (m/s)	6.5	BMEP (MPa)	1.636
Friction Power (kW)	/	Fan Power (kW)	5
Load factor	Power kW	Fuel consum. g/kW.h	Fuel consum. L/h
10%	13.8	315.9	5.19
25%	34.5	226.8	9.32
50%	69	202.7	16.65
75%	103.5	199.3	24.56
85%	117.3	198.5	27.72
100%	138	198.7	32.64
110%	152	199.3	36.06

Air intake system

Intake air temperature rise (°C)	Permitted difference between turbocharger inlet temperature and ambient temperature (this parameter impacts emission, LAT and altitude capability)	≤15
Intake air resistance (kPa)	Clean filter	≤3.5
	Dirty filter	≤6
Air filter mass flow (kg/h)		791
Air mass flow (kg/h)	Rated Power	615
	Standby Power	659
Clear efficiency of air filter (%)		99.9
Recommended Min. diameter of intake pipe (mm)		65

Inter cooling system

Intercooler heat dissipating capacity (KJ/S)	Rated Power	15.6
	Standby Power	17.1
Intercooler efficiency (%)	Rated Power	/
	Standby Power	/
Max. intake temperature (°C)		55

Max. difference between intake temperature and ambient temperature (°C)	30
Permitted max. intake pressure drop of intercooler (kPa)	12
Recommended intercooler radiator cooling area (m ²)	16.8

Exhaust system

Max. exhaust back pressure (kPa)	6±0.5	
Max. exhaust temperature (°C)	Before turbocharger	700
	After turbocharger	550
Recommended muffler mass flow/volume (kg/h)	827	
Exhaust-gas mass flow (kg/h)	Rated Power	643
	Standby Power	689
Recommended Min. diameter of exhaust pipe (mm)	65	
Max. bending moment of turbocharged flange (N·m)	10	

Lubrication system

Volume of oil pan (L)	16	
Oil pressure in normal condition (kPa)	Idle speed	≥120
	Rated Power	300-600
Alarm for low & high oil pressure (kPa)	80/1000	
Temperature range in main oil passage at rated working condition (°C)	80-105	
max. oil temperature (°C)	/	
Max. oil pressure while engine starting (kPa)	800	
Opening pressure of main oil passage pressure limiting valve (kPa)	540-750	
Max. Oil flow (L/min)	47	
Oil consumption	≤0.2%	

Noise and Emission

Emission standard	Off-road stageII	
Exhaust smoke (FSN)	Rated Power	Rb≤2.0
	Standby Power	/
Diesel engine noise dB(A)	112.9	

Fuel system

Injection pump type	Mechanical
Governor	Mechanical/ Electric optional
Steady speed governing factor	≤5%/≤3%

Max supply fuel restriction at rated power conditon (kPa)		≤9
Return restriction in pipe (kPa)		≤12
Max. supply fuel temperature at rated power condition (°C)		≤70
Max. flow of fuel suply (kg/h)	Rated Power	27.46
	Standby Power	30.3
Min. pressure of fuel pump (kPa)		35
Min. Ventilation rate of fuel tank (L/h)		/
Recommended diameter of inlet pipe (mm)		10
Recommended diameter of return pipe (mm)		10

Electrical system

Electrical system voltage (V)		24
Motor power/ working voltage (kW/V)		6/24
Battery charging Alternator/ working voltage (kW/V)		0.98/28
Permitted max. electric resistance of motor control lines (Ω)		0.004
Recommended Min. conductor cross-sectional area (mm ²)		50
The lowest cold starting temperature (°C)	No aided starting device	-10
	Aided starting device	-30

Cooling system

Water pump Transmission ratio		1.4
Min. coolant temperature of engine working (°C)		50
Min. water fill rate (L/min)		3~7
Max. initial fill time (min)		5
Recommended Min diameter of outside water pipe(mm)		42
Min. pressure at water pump inlet at No or only a part of degassing Device (kPa)		-0.02
Min. pressure at water pump inlet at Complete degassing device (kPa)		0
Max. deaeration time(min)		15
Min. expansion tank volume (% total cooling system capacity)		0.15
Min expansion space (% total cooling system capacity)		0.1
Coolant capacity of engine (L)		8
Coolant capacity of radiator (L)		20
High temperature of alarm (°C)		96

Thermostat opening temp./ full open temp. (°C)	76±2 / 90
Min. permitted pressure in cooling system (kPa)	15
Max. permitted external resistance (at rated speed) (kPa)	50

Heat balance test data

Pressure of water in/ water out (kPa / kPa)	Rated Power	29.5/49.2
	Standby Power	30.2/49.7
Coolant mass flow (m ³ /h)	Rated Power	11.1
	Standby Power	11.8
Temperature of water in/ water out (°C/°C)	Rated Power	85.1/89.5
	Standby Power	86.4/91.0
Temperature of intake air : before/after intercooler (°C/°C)	Rated Power	139.3/48.8
	Standby Power	145.8/51.2
Pressure of intake air :before /after intercooler (kPa / kPa)	Rated Power	115.4/115.2
	Standby Power	132.6/132.1
Heat be taken away by Coolant (kJ/s)	Rated Power	57.3
	Standby Power	63.3
Heat be taken away by exhaust gas (kJ/s)	Rated Power	15.6
	Standby Power	17.1
Heat be taken away by intercooler (kJ/s)	Rated Power	90.1
	Standby Power	99.3
Gross Heat of Engine (kJ/s)		184.7/203.5

Mounting system

Inertia of complete engine (kg•m ²)	I _{xx} =24.9	I _{xy} =0.94
	I _{yy} =78.4	I _{yz} =-4.26
	I _{zz} =85.5	I _{xz} =-0.48
Inertia of flywheel (kg•m ²)		1.117
Inertia of crankshaft (including crankshaft gear) (kg•m ²)		0.27
Centroid position mm	X	410.72
	Y	-21.291
	Z	138.77
Permitted static bending moment at flywheel housing flange face		7400